

SIGNATURE SHARE CONTROLLERS

EZ Pro™

SHARE8600W^I



EZPro™ Remote Access Point Controller

* I - International number



Certified by
ICC-ES

WaterSense labeled only
when this product is used with the
Signature Share Intelligent Package



FEATURES

- Remote / Local switch to toggle between Signature Share™ and front control panel of 8600 series.
- Current Sensing for Solenoid Fault Detection (Opens and Overloads)
- Pushbutton for Valve Testing
- Diagnostic LED's for assessing Device State
- Either GSM and CDMA data connections available
- Up to 1 active outputs plus pump
- Programmable pump prime and purge intervals
- Sixteen independent programs
- Individual Station linking to pump output
- Water Budgeting based on Month
- SHARE8600 is accessible from any internet capable computer anywhere in the world
- Compatible with our Signature Share™ platform as well as remotely controlled via iOS devices or Smartphones.
- Remotely monitor sites from one location or an infinite number of locations
- All programs are stored in the controller once downloaded, and are available 24/7 on our secure server
- SHARE8600 requires no extensive backups; we handle all upgrades, support and maintenance
- Upgrades are uploaded seamlessly; when you log on they are ready
- Menus are user friendly and intuitive using graphical user interface

WATER MANAGEMENT FEATURES

- SHARE8600 uses real-time weather data (ET) and transmits it to each controller
- Smart-Water programming allows the controller to precisely irrigate each micro climate individually by programming all agronomical attributes of the irrigated landscape, saving water, time, and expense
- Eliminates requirement to purchase a weather station or other weather services
- Integrated sensor port can accommodate a rain switch

Note:

Data rates may apply given site geography, region of the world and Local Service Providers.

SPECIFICATIONS

DIMENSIONS (H X W X D)

9" (22,9 cm) x 12" (30,5 cm) x 5" (12,5 cm)

Cabinet:

Enclosure: Plastic: Wall Mount

Enclosure Type: Outdoor

Enclosure Rating: IP24*

* Self Certified

of zones:

8, 12, 16, 20, 24

ELECTRICAL:

USA & Canada

INPUT: 120V AC, 60 Hz

OUTPUT: 24V AC, 1.25 Amp

International

INPUT: 230V AC, 50 Hz

OUTPUT: 24V AC, 1.25 Amp

Two AA alkaline batteries
(not included)

CERTIFICATIONS:

FC Part 15 Class B compliant



SIGNATURE CONTROL SYSTEMS, INC.

WORLD HEADQUARTERS

16485 Laguna Canyon Rd., Suite 130, • Irvine • California • 92618
Tel: 949.580.3640 • Fax: 949.580.3645

MANUFACTURING FACILITY

8800 N. Allen Rd., • Peoria • Illinois • 61615
Tel: 949.580.3640 • Fax: 949.580.3645

www.SignatureControlSystems.com

EUROPE & MIDDLE EAST

5 rue de la Vallée Yart • 78640 Saint Germain de la Grange • France
Tel: +33.13.489.9056 • Fax: +33.13.489.6025

USA TOLL FREE:

866.4SIGNATURE