

## IMPACTS

# IMPACTS

IMPACTS

## IMPACTS FAMILY

**6700**



- Includes seven easily interchangeable, color-coded nozzles and 2 low-angle nozzles.
- No tool is required to change nozzles.
- Heavy-duty plastic case with sturdy, reinforced ribbed design.
- Double-weighted arm for slower rotation and increased distance of throw.
- Powerful reverse action.
- Adjustable arm spring for low-pressure and low-gallonage operation.
- Full-circle or adjustable arc 20° to 340°.
- Distance controller diffuser pin.
- Multi-function, pressure-activated wiper seal.
- Inlet filter screen.
- Combination ½" (1,27 cm) or ¾" (1,9 cm) bottom inlet
- Side inlet ½" (1,27 cm)
- Adjustable from 20° - 360°.
- Spacing from 23' – 43' (7 m – 13 m) with a flow rate of 1.5 – 6.3 gpm (5,68 – 23,85 l/min).
- Serviceable through the top of the case.

# IMPACTS

## I370



Beta impact spray heads provide outstanding performance at an affordable price. Made with high impact plastic, they are durable, keeping maintenance to a minimum.

- Includes five easily interchangeable, seven nozzles and 2 low-angle nozzles.
- No tool is required to change nozzles.
- Features ½" (1,27 cm) male threads.
- Non-clog nozzle and straight-through flow design
- Sealed bearing keeps dirt and debris out
- Anti-backsplash arm keeps water off buildings
- Adjust pattern and spray with diffuser pin and exclusive Click-Set® trip collars
- Use I370's for riser installations
- Diffuser pin maintains set spray pattern adjustment
- Perfect for mounting on risers installs.
- Adjustable from 20° - 360°.
- Spacing from 23' – 43' (7 m – 13 m) with a flow rate of 1.5 – 6.3 gpm (5,68 – 23,85 l/min).

## I973



- Ideal for riser installations in planting areas
- ½" (1,27 cm) female threaded inlet
- Made of high-impact corrosion resistant plastic
- Stainless steel bearing and large orifice nozzle
- 40' (12,2 m) diameter coverage.
- 3.4 – 4.4 gpm (12,8 – 16,6 l/min) flow.

## IMPACTS OVERVIEW

### IMPACTS

APPLICATIONS	6700	I 370	I 973
RADIUS 40' (12,2 M)	✓	✓	✓
½" (1,27 CM) INLET			✓
DUAL ½" (1,27 CM) & ¾" (1,9 CM) INLET	✓		
½" (1,27 CM) MALE THREADS		✓	
RESIDENTIAL	✓	✓	
NURSERIES	✓	✓	✓
COMMERCIAL/MUNICIPAL	✓	✓	
HIGH VANDALISM AREAS	✓		
LOW PRESSURE SYSTEMS	✓	✓	✓
RISER MOUNTED		✓	✓
GROUND COVER/SHRUBS	✓	✓	
RECLAIMED WATER	✓	✓	✓
SLOPES	✓	✓	



FOR MORE INFORMATION

### SIGNATURE CONTROL SYSTEMS, INC.

#### WORLD HEADQUARTERS

18 Goodyear • Suite 110  
Irvine • California • 92618  
Tel: 949.580.3640  
Fax: 949.580.3645

**USA Toll Free: 866.4SIGNATURE**

#### MANUFACTURING FACILITY

8800 N.Allen Rd.,  
Peoria • Illinois • 61615  
Tel: 949.580.3640  
Fax: 949.580.3645

#### EUROPE & MIDDLE EAST

5 rue de la Vallée Yart  
78640 Saint Germain de la Grange  
France  
Tel: +33.13.489.9056  
Fax: +33.13.489.6025

#### REGIONAL OFFICES

**ASIA**  
NanXian Plaza • MinZhi Street • Shenzhen,  
Guangdon Province • 518131  
Tel: (86) 136.00419465 • Fax: (86) 755.83275012  
**SOUTH AMERICA**  
Av Paseo Los Bravos 6000 • Lo Barnechea  
Santiago • Chile  
Tel/Fax: +56 229.556220

#### MEXICO, CENTRAL AMERICA

Ribera Escondida 118 • Riberas Del Campestre  
38080 Celaya • Gto. • Mexico  
Tel/Fax: +52 (461) 614.2322

#### AFRICA

P.O. Box 1260 • Strubensvalley 1735  
Roodepoort • South Africa  
Office & Mobile: +27 82 553 9093 • Fax: 086 670 6318

[www.SignatureControlSystems.com](http://www.SignatureControlSystems.com)

99903408